



MFPDP-AOD-1/2", 3/4", 1", 2", 3"



Max Capacity: 300 GPM/1,135 LPM

Max Head: 275' FT/84 M

Max Air Inlet Pressure: 8.4 Bar/121.8 PSI

| |
|-----------|
| Features: |
|-----------|

- | |
|---|
| <ul style="list-style-type: none">• Reliable, Non-Stalling, Non-Lubricated Air Valve Assembly |
| <ul style="list-style-type: none">• Common Center Body for 1" and 2" Pumps |
| <ul style="list-style-type: none">• Easy Access to the Air Motor for Service When Required |
| <ul style="list-style-type: none">• Few Moving Parts |
| <ul style="list-style-type: none">• Epoxy Coated Center Body |
| <ul style="list-style-type: none">• NPT Threaded Ports |

PUMP MODEL AND MATERIAL CODE

Pump model = **RB** 25 AL - PP / TF / TF / PP

Brand
MOSHERFLO

Pump size:
15=1/2" 20=3/4"
25=1" 50=2" 80=3"

Center block material:
AL=Aluminum
PP=Polypropylene
SS=Stainless steel 304

Wetted body material:
AL=Aluminum
PP=Polypropylene
LL=Stainless steel 316

Other materials available upon request

Valve seat material:
TF=Teflon
ST= Santoprene
HY=Hytre
EP=EPDM
BN=Buna-N
GE=Geolast
VT=Viton
PC=PVC
SS=Stainless steel 304
LL=Stainless steel 316
PP=Polypropylene

Valve ball material:
TF=Teflon
ST= Santoprene
HY=Hytre
EP=EPDM
BN=Buna-N
GE=Geolast
VT=Viton
PC=PVC
SS=Stainless steel 304
LL=Stainless steel 316
CM=Ceramic

Diaphragm material:
TF=Teflon
ST= Santoprene
HY=Hytre
EP=EPDM
BN=Buna-N
GE=Geolast
VT=Viton
PU=Polyurethane